NEW ARYLOXY ALKOXYSILANES (I) (U)

DESTRIBUTION STATEMENT A

Approved for public releases
Distribution Unlimited

26 JANUARY 1965

19960503 027

DTIC QUALITY INSPECTED 1

DEPARTMENT OF DEFENSE
PLASTICS TECHNICAL EVALUATION CENTER
PICATINNY ARSENAL. DOVER. N. J.

NOI TR 64-204



# DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

### NOTICE

Requests for additional copies by Agencies of the Department of Defense, their contractors, and other Government agencies should be directed to:

Defense Documentation Center (DDC) Cameron Station Alexandria, Virginia

Department of Defense contractors who have established DDC services or have their 'need-to-know' certified by the cognizant military agency of their project or contract should also request copies from DDC.

All other persons and organizations should apply to:

U.S. Department of Commerce Office of Technical Services Washington 25, D. C.

# NEW ARYLOXY ALKOXYSILANES (I) (U)

Prepared by: James V. Duffy Porter W. Erickson

ABSTRACT: A total of ten new aryloxy alkoxysilanes have been synthesized that are potential glass fiber finish chemicals for several resin systems. The generalized structure for these compounds is:

The R group is usually either methyl or ethyl while R' can be epoxy, amine, alcohol, ester or olefin. These aryloxysilanes were prepared by the partial condensation reaction between resorcinol and the following silanes:  $\beta(3,4-\text{epoxycyclohexyl})$  ethyltrimethoxysilane,  $\beta$ -glycidoxypropyltrimethoxysilane, N,N bis( $\beta$ -hydroxyethyl)- $\beta$ -aminopropyltriethoxysilane,  $\beta$ -aminopropyltriethoxysilane,  $\beta$ -aminopropyltriethoxysilane, vinyltriethoxysilane, vinyltriethoxysilane, vinyl-tris( $\beta$ -methoxyethoxy)silane,  $\beta$ -methoxyethoxysilane,  $\beta$ -methoxyethoxysilane,  $\beta$ -cyclohexenetriethoxysilane and allyltriethoxysilane.

PUBLISHED APRIL 1965

APPROVED BY:

F. Robert Barnet, Chief Non-Metallic Materials Division

CHEMISTRY RESEARCH DEPARTMENT
U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

26 January 1965

# NEW ARYLOXY ALKOXYSILANES (I)

A series of new alkoxy derivatives of NOL-24 (U. S. Patent 2,720,470) have been synthesized and are discussed in this report. These glass finishes in addition to being more stable compounds than NOL-24 also contain various new reactive functional groups.

These compounds have not been isolated to date due to their reactive nature. Consequently, their structural formulae have not been determined but are assumed, based on the types of reactions expected due to their similarity to other known chemical reactions.

This is part of the work performed under POLARIS Research Task PR-4.

R. E. ODENING Captain, USN

Commander

ALBERT LIGHTBODY

By direction

		CONTENTS						
INTRODUCTION	• • • • • • • •		• • • • • •		• • • • •	• • • •	• • •	1
HISTORICAL	• • • • • • • •							2
EXPERIMENTAL WORK AND	D RESULTS			• • • • •		· • • •		3
DISCUSSION OF POSSIB	LE SIDE RI	EACTIONS	• • • • •					7
CONCLUSIONS	• • • • • • • •				• • • • •		• • •	9
RECOMMENDATIONS	• • • • • • • •	• • • • • • • • • •	• • • • •			· • • •		9
APPENDIX A Equipment	• • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	••••		••••	· • • •		A-1
APPENDIX B Materials			••••			, <b></b>	•• :	B <b>-</b> 1
		ILLUSTRATI	ons					
Figure		Title						
1 2		Spectra of Equipment	Model	Compo	und			


### REFERENCES

- (a) Erickson, P. W., Silver, I., and Perry, H. A. Jr., NAVORD Report 3811 (1954)
- (b) Erickson, P. W., Notebook No. 80-3988 p. 1, Naval Ordnance Laboratory (1955)
- (c) Peppard, D. F., Brown, W. G., and Johnson, W. C., J. Am. Chem. Soc. 68, 73 (1946)
- (d) Malatesta, L., Gazz. Chem. Ital., 78, 747 (1948)
- (e) Voronkov, M. G., and Karpenko, G. B., J. Gen. Chem. U.S.S.R., 27, 361, (1957)
- (f) Mehrotra, R. C., and Pant, B. C., Jour. Indian Chem. Soc., 40, No. 8, 623 (1963)
- (g) Shechter, L., and Wynstra, J., Ind. and Eng. Chem., 48, No. 1, 86, (1956)
- (h) Boyd, D. R., and Marle, E. R., J. Chem. Soc., 105, 2117 (1914)
- (i) Patat, E., Cremer, E., and Bobleter, O., J. Polymer Sci., 12, 489 (1954)

### INTRODUCTION

Chemical finishes are widely used to improve the strength properties of glass fiber plastic composites. These finishing materials can be divided into three general classes of compounds: alkoxysilanes, chrome complexes and chlorosilanes. NOL-24 is an aryloxy chlorosilane which was first prepared at these laboratories by Erickson in 1955 (ref. (a)). This material is an excellent glass fiber finish for epoxy, phenolic, melamine and polyester glass reinforced composites and provides retention of strength after severe exposure to moist environments. Flexural strengths as high as 150,000 psi have been reported for epoxy laminates containing NOL-24 finished glass cloth (Style 181) with usual wet strength retentions up to 95 percent (ref. (b)). In spite of its superior performance in reinforced plastics, NOL-24 is commercially impractical because of its susceptibility to hydrolysis by moisture. Furthermore, it requires the use of flammable solvents and produces a corrosive by-product (hydrogen chloride) which further limit its usefulness.

In an effort to increase the practicality of NOL-24 as a glass finish, attempts have been made to modify the structure in such a way as to eliminate the inherent disadvantages without affecting its excellent finish properties. Initially, the approach taken was to convert the existing chlorosilane finish to the more stable and less corrosive alkoxysilane or ester derivative. Reactions with sodium acetate, sodium methylate and ethyl acetate were studied in an effort to prepare the



This indirect approach proved to be infeasible but led to a direct preparative route to the desired compounds. This report discusses ten new aryloxy alkoxysilanes which have been synthesized during the course of this investigation. All of these new materials are structural derivatives of NOL-24 and in addition possess increased stability and resistance to hydrolysis. The finish properties of these compounds are being evaluated and will be discussed in a subsequent report.

# HISTORICAL

It has been known for sometime that alkoxysilanes transesterify with aliphatic alcohols and this reaction has been used as a convenient method for synthesizing higher tetraalkoxysilanes (ref. (c)). Malatesta (ref. (d)) in 1948 suggested the possibility of transesterifying tetraethyl orthosilicate with phenol in the presence of aluminum or sodium ethylate. However, it was not until 1956 that Voronkov and Karpenko (ref. (e)) used this reaction in the preparation of tetraaroxysilanes about which they stated "in contrast to alkoxysilanes - aroxysilanes are hardly mentioned in the literature". A typical reaction involved the preparation of tetra(o-allylphenoxy)silane:

In a more recent work, Mehrotra and Pant (ref. (f)) showed that dimethyldiethoxysilane will react with salicylic acid to form the cyclic product

All of this previous work led us to believe that resorcinol would react with various commercially available alkoxy silanes to yield new NOL-24 derived finishes. A general mechanism for this reaction can be written as follows:

The R group generally represents methyl or ethyl while R' can be any organic moiety containing reactive functional groups. Indeed this method was used to prepare directly the alkoxy derivative of NOL-24:

### EXPERIMENTAL WORK AND RESULTS

The details of the procedure and materials used are shown in Appendix A and B respectively.

A model reaction involving a resorcinol derivative (m-methoxyphenol) and an alkoxysilane was studied initially to determine the feasibility of this approach. The reaction between m-methoxyphenol and  $\beta$ -carbethoxyethyltriethoxysilane was carried to 93% completion to yield the following product:

# 5.

+C2H5OH

This particular phenol was selected because the product did not contain residual hydroxyl and could be purified by distillation without further polymerization. Fractional distillation at a temperature of 166-168°C/0.45 mm yielded a compound having the following carbon-hydrogen analysis:


	Theoretical	Found		
Carbon	56.12	56.04		
Hydrogen	7.65	7.24		

The infra-red spectra (Fig. 1) of the initial and final reaction mixtures show loss of absorption at 3400 cm<sup>-1</sup> which corresponds to phenolic hydroxyl. The spectra further show decreased -CH<sub>2</sub>- absorption in the region of 3000-2800 cm<sup>-1</sup> and below 1500 cm<sup>-1</sup> due to the loss of ethanol from the reaction mixture. The retention of the doublet at 1725 cm<sup>-1</sup> can be attributed to the carbethoxy group which does not take part in the reaction. These results show that the condensation reaction takes place between the phenolic hydroxyl and ethoxy silane group.


This model reaction is used as the basis for writing structures for the products obtained from other resorcinol-alkoxysilane reactions. However, in the case of these materials, we are dealing with reactive intermediates which can undergo further reaction leading to polymer formation. The presence of residual hydroxyl in these reaction products is confirmed by the strong infra-red absorption in the region of 3400 cm<sup>-1</sup>. These hydroxyl groups cause the compounds to have very high boiling points even at high vacuums. The result of these factors is that the reaction temperature is reached before the compound boils and polymerization occurs.


The capability of obtaining high vacuum has been now realized and further attempts at isolation of these compounds by fractional distillation will be made. Another possible approach to this problem of separation is to use a blocking group such as  $-Si(CH_3)_3$  to inactivate the phenolic hydroxyl. This compound could be distilled and then by selective hydrolysis it might be possible to obtain the desired material.


In view of the existing difficulties the materials which have been prepared have not yet been isolated as pure compounds. It is felt, however, that since the reaction is a simple condensation (see Discussion) the products obtained in most cases should be sufficiently pure to permit their evaluation as glass finishes. The compounds prepared include the following:



-









ost - (сн2)2соос2H5 он

OC2H5

OC2H5





14.

OC2H5

3-cyclobexenetriethoxysilane

13.

# DISCUSSION OF POSSIBLE SIDE REACTIONS

Single reaction products have been written in each case which is perhaps an oversimplification of the actual situation. It is advisable, therefore, to review some of the possible side reactions which can occur during the preparation of several of these materials.

Shechter and Wynstra (ref. (g)) have shown that two types of reaction are possible between phenol and glycidyl ether. The initial reaction is that of the phenolic hydroxyl with epoxide and the subsequent reaction of the aliphatic alcohol generated in the first reaction with epoxide. These reactions can be written as follows:

17.

Noncatalyzed at 200°C the rate of the second reaction was more rapid than that of phenolic hydroxyl with epoxide. This is quite significant

when one realizes that the initial aliphatic hydroxyl concentration was zero and became finite only after some epoxide reacted with phenol. It was concluded that the phenol acted as a catalyst for the second reaction. The base catalyzed reaction of phenol with glycidyl ether proceeded at a lower temperature to the exclusion of any alcohol-epoxide reaction. A mechanism for this reaction was proposed by Boyd and Marle (ref. (h)) and Patat, Cremer and Bobleter (ref. (i)). This mechanism can be represented as follows:

By analogy, one could write similar reactions between resorcinol and epoxysilanes (reactions 6 and 7) and predict similar side product formation. The side reactions in this case would be in direct competition with the phenolic hydroxyl alkoxysilane reaction. A further complication is the fact that both reactions are base catalyzed. Our work shows qualitatively that at 110-120°C the sodium methylate catalyzed reaction of resorcinol and 0-glycidoxypropyltrimethoxysilane (reaction 7) produced a polymeric gel while the same reaction at 180-200°C without catalyst yielded a liquid product. It appears that the catalyzed reaction at lower temperatures favored more of the resorcinol-epoxide reaction than the noncatalyzed reaction at higher temperatures. In the reaction of resorcinol with β(3,4-epoxycyclohexyl)ethyltrimethoxysilane (reaction 6), polymerization occurred at 180°C without catalyst while a liquid was obtained in the sodium methylate reaction at 110-130°C. The results indicated here were of a qualitative nature and no attempt was made to determine the extent of each of the possible reactions. The infra-red data in the region of epoxy absorption (830 cm-1) in the case of the liquid products do not exhibit any appreciable decrease in intensity which would indicate very little side reaction had taken place.

Another possible side reaction which should be considered involves the reaction of resorcinol and \( \delta \)-aminopropyltriethoxysilane (reaction 9). This product was the only finish in this particular series of compounds that exhibited water miscibility. The solution of this compound is probably succeeded by water hydrolysis to a siloxane type polymer. On the basis of this solubility information it is felt that the compound in question is probably in the following ionized form:

In the case of the product from N,N bis( $\beta$ -hydroxyethyl)-  $\sqrt{\phantom{a}}$ -aminopropyltriethoxysilane (reaction 8) there is no apparent miscibility in water and the hydrolysis product is a polymer. The ionization of the product in this case is probably inhibited by the difference in basicity of these amines and by the fact that the unreacted phenolic hydroxyl can take part in hydrogen bonding with the alcohol groups.

In regard to the reaction of the unsaturated and ester alkoxy silanes with resorcinol we feel that no appreciable side reactions take place under the conditions stated.

### CONCLUSIONS

The preparation of derivatives of NOL-24 via the reaction of resorcinol with alkoxysilanes is a general reaction which can be applied to a variety of starting materials. Derivatives of NOL-24 which contain epoxy, ester, alcoholic, amino and olefin groups have been synthesized using this method. These new finishes are stable compounds that are resistant to hydrolysis by moisture and suitable for commercial application. The performance of these new compounds as finishes will be evaluated in several resin systems and reported on at a later date.

### RECOMMENDATIONS

All of the finishes discussed in this report are derived from meta isomer of dihydroxybenzene commonly known as resorcinol. It would also be of value to prepare derivatives of the ortho (pyrocatechol) and para (hydroquinone) isomers and study their properties. Steric effects in the aromatic portion of these molecules could result in modifications in the performance of the finish chemicals and should be studied.

Another area in which effort should be directed is in the preparation of other functional derivatives based on the resorcinol structure. The phenolic hydroxyl could be replaced by other active groups like alcoholic, amine or acid moieties. These groups are known to be very reactive with

epoxy resins for example and should therefore promote stronger bonding between the resin and the finished glass surface. Other polyfunctional derivatives of resorcinol should also be synthesized and evaluated as potential chemical finishes. The following compounds are typical examples:

# ACKNOWLEDGEMENT

The author wishes to express his appreciation to Mr. Arthur B. Harris for his able assistance in the experimental portion of this work.

### APPENDIX A

### EQUIPMENT

- A-1. The equipment used to prepare these finishes (Fig. 2) consisted of a 100 ml one-necked flask which was connected with a heated Dean-Stark trap and condenser. Heating was accomplished with a silicone oil bath (Down Corning 550) which was stirred magnetically and could be operated continually at 200°C. The contents of the flask were stirred by a Teflon coated magnet bar. The Dean-Stark trap was heated by means of nichrome wire (0.015") wrapped in asbestos so that the alcohol formed during the course of the reaction could be removed rapidly. The rapid removal of the alcohol insured the proper displacement of the reaction equilibrium and permitted the reaction to proceed at lower temperatures. The volume of alcohol distilled was measured directly in the Dean-Stark trap.
- A-2. The Perkin-Elmer model 337 grating infra-red spectrophotometer was used to obtain spectra of the starting silane, the initial reaction mixture and the final reaction product. This instrument is a double beam spectrophotometer with two standard scanning speeds and a total range of 2.5-25 microns (4000-400 cm<sup>-1</sup>).

### APPENDIX B

### MATERIALS

B-1. The chemicals used in this study consisted of: resorcinol - Fisher certified reagent-R17 sodium methylate - Fisher purified-S335 1,3-diaminobenzene (Cl)-General Aniline Dye and Film Co. m-methoxyphenol - Fisher 223 Epon 828 resin - Shell Chemical Co. 3(3,4-epoxycyclohexyl)ethyltrimethoxysilane (Y4086) - Union Carbide X-glycidoxypropyltrimethoxysilane (Y4087) - Union Carbide N,N bis( $\beta$ -hydroxyethyl)- $\delta$ -aminopropyltriethoxysilane (Y2967) -Union Carbide \* -aminopropyltriethoxysilane (AllOO) - Union Carbide S-carbethoxyethyltriethoxysilane (A-1911) - Union Carbide vinyltriethoxysilane (Al51)- Union Carbide vinyltris(\beta-methoxyethoxy) silane (Al72) - Union Carbide 7 -methacryloxypropyltrimethoxysilane (Al74) - Union Carbide 3-cyclohexenetriethoxysilane (Y4407) - Union Carbide

allyltriethoxysilane - Linden Laboratories, Inc.




FIG. I m - METHOXYPHENOL-B-CARBETHOXYETHYLTRIETHOXYSILANE




FIG. 2 REACTION EQUIPMENT USED IN THE PREPARATION OF ARYLOXY ALKOXYSILANES

### DISTRIBUTION

Copies

Chief, Bureau of Naval Weapons

RMMP-11 (I. Silver)

RRMA (N. E. Promisel)

RRMA-5 (P. Stone)

RRMA-34 (C. Bersch)

RRMA-32 (M. Stander)

RRMA-35 (J. Gurtowski)

DIS-3 (Library)

14

Director, Special Projects Office SP-27304 (H. Bernstein)

Chief, Eureau of Ships

Code 634-c (W. Graner)

(J. Alfers)

Chief of Naval Research

Navy Department

Washington, D. C. 30260

Attn: Dr. Lewis Butz

Director, Naval Research Laboratory

Washington, D.C.

Attn: J. Kies

Dr. W. Zisman, Code 6100

20390

Dr. I. Wolock, Code 6213

Commander

U. S. Naval Ordnance Test Station

China Lake, California

Commander

U. S. Naval Ordnance Test Station

3203 E. Foothill Boulevard

Pasadena, California

Commander

U. S. Naval Ordnance Laboratory

Corona, California

Attn: Dr. Charles P. Haber

Materials Laboratory

New York Naval Shipyard

Brooklyn 1, New York

Attn: N. Fired

### DISTRIBUTION

Copies

Commander

U. S. Naval Air Development Center Johnsville, Pennsylvania

Office of the Chief of Ordnance
Department of the Army
Pentagon Building
Washington, D. C. 20350
Attn: ORDTA
ORDTE
ORDTB (Materials Section)

Commanding Officer
Picatinny Arsenal
Dover, New Jersey
Attn: Plastics Laboratory

Plastics Technical Evaluation Center Picatinny Arsenal Dover, New Jersey

U. S. Army Engineer Research and Development Laboratories
Ft. Belvoir, Virginia
Attn: STINFO Branch

Director

Air Force Materials Laboratory
Wright-Patterson AFB, Ohio 45433
Attn: MAG

MANC (Plastics and Composites Branch)
MANC (S. Litvak)

Chief

AFSC Scientific and Technical Liaison Office c/o Department of the Navy Room 3710 Main Navy Building

Commander

Air Proving Ground Center Eglin AFB, Florida 32542 Attn: PGAPI

Commander

Ballistic Systems Division
Norton AFB, California 92409

Attn: BSAP

### DISTRIBUTION

Director
Air Force Office of Scientific Research
T-D Building
Washington, D. C. 20333
Attn: SRIL

Director
National Aeronautics and Space Administration
1512 H Street, N. W.
Washington 25, D. C.
Attn: Bernard Achhammer

University of Dayton Research Institute Dayton 9, Ohio Attn: Research Librarian

Scientific and Technical Unit CINCUSNAVEUR, Frankfurt APO 757 New York, New York

Defense Documentation Center Cameron Station Alexandria, Virginia

20

Copies

Security Classification			CAPACITY CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CO		
OCUMENT COMES (Security classification of title, body of abstract and indexin	NTROL DATA - R&	D stered when t	he overall report is classified)		
ORIGINATING ACTIVITY (Corporate author)		2a. REPOR	RT SECURITY CLASSIFICATION		
1. ORIGINATING ACTIVITY (Computate author)		Unclassified			
		2 b. GROUP			
U. S. Naval Ordnance Laboratory White Oak, Maryland		20.000			
3. REPORT TITLE					
NEW ARYLOXY ALKOXYSILANES (I) (U)					
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)					
Progress January 1964 - June	1964				
5. AUTHOR(S) (Last name, first name, initial)					
Duffy, James V.					
Erickson, Porter W.					
			Tat as asset		
6. REPORT DATE	74. TOTAL NO. OF F	AGES	7b. NO. OF REFS		
26 January 1965	10		У		
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S R	EPORT NUM	BER(S)		
6. PROJECT NO. NOL-732/SP-004	NOLTR 64-204				
c.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned				
	this report)				
d.					
10. A VAIL ABILITY/LIMITATION NOTICES					
Qualified requesters may obtain c	opies of this	report :	from DDC.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MIL	ITARY ACT	IVITY		
-	NOL White Oak, Maryland		ryland		
42 ADSTRACT					
A total of ten new aryloxy alkoxy potential glass fiber finish chem aryloxysilanes were prepared by tresorcinol and the following silatrimethoxysilane, -glycidoxypro ()-aminopropyltriethoxysilane, B-carbethoxyethyltriethoxysilane, ethoxy)silane, ()-methacryloxypro silane and allyltriethoxysilane.	micals for sever the partial con anes: β(3,4-ep opyltrimethoxys { -aminopropylt . vinvltriethox	eral residensation oxycyclesilane, criethox	in systems. These on reaction between ohexyl)ethyl- N,N bis(β-hydroxyethyl) ysilane, , vinyl-tris(β-methoxy-		

14.	LIN	LINKA		LINKB		LINKC	
KEY WORDS		ROLE	WT	ROLE	wT	ROLE	₩T
aryloxy silanes alkoxy silanes silanes glass finishes finishing chemicals coupling agents — Ac	e Janishis						

### INSTRUCTIONS

- ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.
- 2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.
- 3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.
- 4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.
- 5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
- 6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.
- 7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.
- 8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.
- 8b, &c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.
- 9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).
- 10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through
- (5) "All distribution of this report is controlled Qualified DDC users shall request through

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known

- 11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.
- 12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.
- 13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

1. Finishes -  2. Glass cloth - Finishes 3. Silanes 4. Arlexy chloresilane I. Title II. Duffy, James V. III. Ericksen, Perter W., jt. author IV. Preject unclassified.	l. Finishes - NOL, 24 2. Glass 2. Glass 3. Slanes 4. Arlexy Arlexy OMBeresiane I. Title II. Duffy, James V. III. Ericksen, jt. auther IV. Preject unclassified.
Naval Ordnamce Laboratory, White Oak, Md.  (NOL technical report 64-204)  NEW ARYLOXY ALKOXYSILANES (1), by James V.  Duffy and Perter W. Ericksem. 26 Jam. 1965.  v.p. charts. NOL task 732/SP-004.  UNCLASSIFIED  A tetal of ten mew arylexy alkexysilanes have been synthesized that are petential glass fiber fimish chemicals for several resin systems. These arylexysilanes were prepared by the partial condensation reaction between respectively and the following silanes: $\beta(3,4-$ epoxycolohexyl)ethyltrimethexysilane, $\gamma$ -circleboxycilane, by the following silanes: $\gamma$ -circleboxycilane, vanyltriethexysilane, $\gamma$ -circleboxycilane, vinyltriethexysilane, vinyltriethexysilane.	Naval Ordnance Laberatery, White Oak, MG.  (NOL technical repert 64-204)  NEW ARYLOYY ALKOYSTIANES (1), by James V.  Duffy and Perter W. Ericksa. 26 Jan. 1965.  v.p. charts. NOL task 732/SP-004.  UNCLASSIFIED  A tetal of ten new arylexy alkexysilanes have been synthesized that are petential glass fiber fimish chemicals for several resin systems. These arylexysilanes were propared by the partial condensation reaction between resocianl and the following silanes: \$(3,4-epsxycyclehexyl)ethyltrimethexysilane, v-glycidexyprepyltrimethexysilane, v, N bis(\$-hydrexychyl).  xycthyl).  y -anineprepyltridethexysilane, v-emineprepyltriatethexysilane, vinyltrichexysilane, vinyltrichexys
1. Finishes - NOL, 24 2. Glass Glass Gloth - Finishes 3. Silanes 4. Arlexy Chleresilane II. Title III. Duffy, James V. III. Ericksen, jt. auther IV. Preject UN. Preject Unclassified.	1. Finishes - NOL, 24 2. Glass 6 clath - Finishes 3. Silanes 4. Arlexy Chlery Chleresilane I. Title II. Duffy, James V. III. Ericksen, Perter W., jt. auther IV. Preject umclassified.
Naval Ordnance Laberatery, White Oak, Mi.  (NOL technical repert 64-204)  NEW ARYLOXY AIKOXYSILANES (I), by James V. Duffy and Perter W. Ericksen. 26 Jam. 1965.  v.p. charts. NOL task 732/SP-004.  A tetal of ten mew arylexy alkexysilanes have been synthesized that are petential glass fiber finish cheanicals for several resin systems. These arylexysilanes were prepared by the partial condensation reaction between resorginel and the following silanes: 8(3,4-epsxyprepyltrimethexysilane, V-glycidexyprepyltrimethexysilane, V-glycidexyprial thexysilane, V-amineprepyltriethexysilane, V-amineprepyltriethexysilane, V-amineprepyltriethexysilane, vinyltriethexysilane, vinyltriethexysilane.	Naval Ordnance Laberatery, White Oak, Md.  (NOL technical repert 64-204)  NEW AFYLOXY ALKOXYSILANES (1), by James V.  Duffy and Perter W. Erickson. 26 Jan. 1965.  v.p. charts. NOL task 732/SP-004.  UNCLASSIFIED  A tetal of ten mew arylexy alkexysilanes have been synthesized that are petential glass fiber finish chemicals for several resin sys- tens. These arylexysilanes were propared by the partial condensation reaction between re- sercinel and the fellowing silanes: p(3,4 epexycolehexyl) ethyltrimethexysilane, y-gly- cidexypropyltrimethexysilane, N,N bis(B-bydre- xyethyl)-y-aminepropyltricthexysilane, y-gm- inepropyltriethexysilane, y-aminepropyltriethexysilane, y-min- tris(B-methexyethexy) silane, y-emethacysilane, vinyl- tris(B-methexyethexy) silane, y-methacyre- propyltrimethexysilane, y-aminethexysilane, vinyl- tris(B-methexyethexy) silane, y-methacyr- propyltrimethexysilane, 3-cyclehexemetrie- thexysilane and allyltriethexysilane.